



AUTOMATIC BELT TENSIONING

Automatic belt tensioning keeps the drive belt under tension, whether it is cold or warm and whether the belt is new or already run in. Once adjusted, the tension is automatically maintained at the set level.




A ROBUST AND MULTIPURPOSE HOOD

The rear hood is adjustable. Adjust it to the minimum for shredding slightly dense vegetation or maximum product recycling. Adjust it to the maximum when shredding dense vegetation or if you want to work faster, while limiting the power input.

DOUBLE METAL FRAME

The cutting chamber on features a double-skinned construction (5 + 4 mm) The toothed counter blades allow the machine to mulch even the more voluminous residues and thicker branches into fine pieces. The body is reinforced with the addition of a sheet metal internal housing for extra strength.



Kosiarka bijakowa Schlegelmäher Flail mowers	<u>↓</u>	min HP (kW)	cat	540	1000	5 Omm	O. Sanda	1	+	→ mm	hydraulic	Kg
KDX 180+ Profi	1,80	60(45)	. I/II	540	1000 options	127	SKF STANDART	26	859 941	628 1172	- STANDART -	547
KDX 200+ Profi	2,00	70(52)						28	1075 925	726 1274		579
KDX 220+ Profi	2,20	80(60)						32	1075 1125	726 1474		606
KDX 240+ Profi	2,40	90(67)						34	1175 1225	826 1574		636